


Metrische wartelkoppeling 24° conus en o-ring type DF
DIN2353



Modellen:

Serie L							
Bestelnummer	slangmaat	leidingmaat	F	H	L	S	max. werkdruk bar*
C12DF-06L-03	3/16	6L	M12x1,5	21	46	14	280
C14DF-08L-03	3/16	8L	M14x1,5	21	46	17	280
C12DF-06L-04	1/4	6L	M12x1,5	23	51	17	280
C14DF-08L-04	1/4	8L	M14x1,5	22	50	17	280
C16DF-10L-04	1/4	10L	M16x1,5	24	52	19	280
C18DF-12L-04	1/4	12L	M18x1,5	25	52	22	280
C14DF-08L-05	5/16	8L	M14x1,5	27	54	19	280
C16DF-10L-05	5/16	10L	M16,1,5	24	52	19	280
C18DF-12L-05	5/16	12L	M18x1,5	24	52	22	280
C16DF-10L-06	3/8	10L	M16x1,5	23	54	19	280
C18DF-12L-06	3/8	12L	M18x1,5	24	54	22	280
C22DF-15L-06	3/8	15L	M22x1,5	24	54	27	280
C22DF-15L-08	1/2	15L	M22x1,5	24	57	27	280
C26DF-18L-08	1/2	18L	M26x1,5	26	59	32	210
C26DF-18L-10	5/8	18L	M26x1,5	27	62	32	210
C30DF-22L-10	5/8	22L	M30x2	28	64	36	210
C30DF-22L-12	3/4	22L	M30x2	31	71	36	210
C36DF-28L-16	1	28L	M36x2	32	83	41	165
C45DF-35L-20	1 1/4	35L	M45x2	36	94	50	125
C52DF-42L-24	1 1/2	42L	M52x2	37	102	60	100
Serie S							
Bestelnummer	slangmaat	leidingmaat	F	H	L	S	max. werkdruk bar*
C14DF-06S-04	1/4	6S	M14x1,5	23	51	17	450
C16DF-08S-04	1/4	8S	M16x1,5	22	50	19	450
C18DF-10S-04	1/4	10S	M18x1,5	24	52	22	450
C18DF-10S-05	5/16	10S	M18x1,5	24	52	22	350
C20DF-12S-05	5/16	12S	M20x1,5	24	52	24	350
C18DF-10S-06	3/8	10S	M18x1,5	25	55	22	445
C20DF-12S-06	3/8	12S	M20x1,5	24	54	24	445
C22DF-14S-06	3/8	14S	M22x1,5	28	58	27	445
C22DF-14S-08	1/2	14S	M22x1,5	28	61	27	415
C24DF-16S-08	1/2	16S	M24x1,5	29	62	30	415
C30DF-20S-10	5/8	20S	M30x2	33	69	36	350
C30DF-20S-12	3/4	20S	M30x2	36	76	36	350
C36DF-25S-12	3/4	25S	M36x2	38	78	46	350
C36DF-25S-16	1	25S	M36x2	40	91	46	280
C42DF-30S-16	1	30S	M42x2	40	91	50	280
C42DF-30S-20	1 1/4	30S	M42x2	41	99	50	210
C52DF-38S-20	1 1/4	38S	M52x2	45	103	60	210
C52DF-38S-24	1 1/2	38S	M52x2	46	110	60	185

* Attentie: let ook op de maximale werkdruk van de slang.