



ORFS 90° wartelkoppeling vlakke afdrichting type ORFS90



Modellen:

Bestelnummer	slangmaat	F UNF	H	L	K	S	max. werkdruk bar*
C09ORFS90-04	1/4	9/16	27	55	21	17	450
C11ORFS90-04	1/4	11/16	27	55	24	22	450
C11ORFS90-05	5/16	11/16	29	57	25	22	350
C11ORFS90-06	3/8	11/16	31,5	62	24,5	22	450
C13ORFS90-06	3/8	13/16	31	61	30	24	450
C13ORFS90-08	1/2	13/16	39	72	31	24	415
C16ORFS90-08	1/2	1	39	72	34	30	415
C19ORFS90-08	1/2	1 3/16	39	72	42	36	415
C16ORFS90-10	5/8	1	45	81	35	30	350
C19ORFS90-10	5/8	1 3/16	45	81	42	36	350
C19ORFS90-12	3/4	1 3/16	55	95	45	36	350
C23ORFS90-12	3/4	1 7/16	55	95	49	41	350
C23ORFS90-16	1	1 7/16	71	122	55	41	350
C27ORFS90-20	1 1/4	1 11/16	86	143	63	50	210

ORFS koppeling met uitwendige draad vlakke afdrichting type ORMS (exclusief O-ring)



Modellen:

Bestelnummer	slangmaat	F UNF	H	L	S	O-ring	max. werkdruk bar*
C09ORMS-04	1/4	9/16	23,5	51,5	17	OR7,66X1,78	450
C11ORMS-04	1/4	11/16	25,5	53,5	19	OR9,25X1,78	450
C11ORMS-05	5/16	11/16	25,5	53,5	19	OR9,25X1,78	350
C11ORMS-06	3/8	11/16	25,5	56	19	OR9,25X1,78	450
C13ORMS-06	3/8	13/16	28,5	59	22	OR12,42X1,78	450
C16ORMS-06	3/8	1	33	63,5	27	OR15,6X1,78	450
C13ORMS-08	1/2	13/16	29,5	62,5	27	OR12,42X1,78	415
C16ORMS-08	1/2	1	34	67	27	OR15,6X1,78	415
C19ORMS-08	1/2	1 3/16	37	70	32	OR18,77X1,78	415
C16ORMS-10	5/8	1	34	70	27	OR15,6X1,78	350
C19ORMS-10	5/8	1 3/16	37	73	32	OR18,77X1,78	350
C19ORMS-12	3/4	1 3/16	38	78,5	32	OR18,77X1,78	350
C23ORMS-12	3/4	1 7/16	42,5	83	41	OR23,52X1,78	350
C23ORMS-16	1	1 7/16	44	95	41	OR18,77X1,78	280
C27ORMS-20	1 1/4	1 11/16	46	104	46	OR29,87X1,78	210

* Attentie: let ook op de maximale werkdruk van de slang.