


FOS-S45

METRIC FEMALE 24° O'RING CONE - 45° ELBOW - HEAVY DUTY - SLIP-ON NUT
FEMMINA METRICA OGIVA 24° O'RING - CURVA A 45° - SERIE PESANTE - DADO LIBERO

DKOS45




TIEFFE Part.N.	Hose Size			METRIC 24° Connection		Dimensions (mm)					Maximum W.P.	
	DN	Inch	Dash	F	Pipe	H	L	K	S	O-RING	bar	PSI
CH12FOS20S45B	19	3/4"	-12	M 30x2	20S	67	129	29	36	16,3x2,4	420	6000
CH12FOS25S45B	19	3/4"	-12	M 36x2	25S	66	128	30	46	20,3x2,4	420	6000
CH16FOS25S45B	25	1"	-16	M 36x2	25S	81	154	33	46	22x2	380	5500
CH16FOS30S45B	25	1"	-16	M 42x2	30S	81	154	33	50	25,3x2,4	380	5500
CH20FOS30S45B	31,5	1 1/4"	-20	M 42x2	30S	99	187	39	50	25,3x2,4	325	4700
CH20FOS38S45B	31,5	1 1/4"	-20	M 52x2	38S	100	188	40	60	33,3x2,4	325	4700
CH24FOS38S45B	38	1 1/2"	-24	M 52x2	38S	116	210	44	60	33,3x2,4	290	4200

FOS-S90

METRIC FEMALE 24° O'RING CONE - 90° ELBOW - HEAVY DUTY - SLIP-ON NUT
FEMMINA METRICA OGIVA 24° O'RING - CURVA A 90° - SERIE PESANTE - DADO LIBERO

DKOS90



TIEFFE Part.N.	Hose Size			METRIC 24° Connection		Dimensions (mm)					Maximum W.P.	
	DN	Inch	Dash	F	Pipe	H	L	K	S	O-RING	bar	PSI
CH12FOS20S90B	19	3/4"	-12	M 30x2	20S	55	117	60	36	16,3x2,4	420	6000
CH12FOS25S90B	19	3/4"	-12	M 36x2	25S	55	117	60	46	20,3x2,4	420	6000
CH16FOS25S90B	25	1"	-16	M 36x2	25S	71	144	71	46	22x2	380	5500
CH16FOS30S90B	25	1"	-16	M 42x2	30S	71	144	71	50	25,3x2,4	380	5500
CH20FOS30S90B	31,5	1 1/4"	-20	M 42x2	30S	90	177	85	50	25,3x2,4	325	4700
CH20FOS38S90B	31,5	1 1/4"	-20	M 52x2	38S	90	177	86	60	33,3x2,4	325	4700
CH24FOS38S90B	38	1 1/2"	-24	M 52x2	38S	107	201	98	60	33,3x2,4	290	4200