




Persslangkoppelingen R1A, R1AT, R2A, R2AT en 4SP


JIC 90° wartelkoppeling met 37° conus type J90



Modellen:

Bestelnummer	slangmaat	F UNF	H	L	K	S	max. werkdruk bar*
C19J90-12	3/4	1 3/16	55	95	54	36	280
C21J90-12	3/4	1 5/16	55	95	56	38	210
C17J90-16	1	1 1/16	71	122	71	32	280
C21J90-16	1	1 5/16	71	122	70	38	210
C26J90-16	1	1 5/8	71	122	70	50	210
C26J90-20	1 1/4	1 5/8	86	143	82	50	210
C30J90-20	1 1/4	1 7/8	86	143	82	55	140
C30J90-24	1 1/2	1 7/8	102	167	96	55	140

JIC koppeling met uitwendige draad 37° conus type JM



Modellen:

Bestelnummer	slangmaat	F UNF	H	L	S	max. werkdruk bar*
C07JM-04	1/4	7/16	25,5	53,5	12	400
C08JM-04	1/4	1/2	25,5	53,5	14	400
C09JM-04	1/4	9/16	26,6	54,6	15	350
C08JM-05	5/16	1/2	25,5	53,5	14	350
C09JM-05	5/16	9/16	26,6	54,6	15	350
C12JM-05	5/16	3/4	29,7	57,5	19	350
C09JM-06	3/8	9/16	26,6	57,1	15	350
C12JM-06	3/8	3/4	29,7	60,2	19	350
C14JM-06	3/8	7/8	34,3	64,8	24	350
C12JM-08	1/2	3/4	30,7	63,7	19	350
C14JM-08	1/2	7/8	35,3	68,3	24	350
C17JM-08	1/2	1 1/16	38,9	71,9	27	350
C14JM-10	5/8	7/8	35,5	71,3	24	350
C17JM-10	5/8	1 1/16	39,1	74,9	27	350
C17JM-12	3/4	1 1/16	39,9	80,4	27	350
C19JM-12	3/4	1 3/16	41,6	82,1	32	280
C21JM-12	3/4	1 5/16	42,1	82,6	34	280
C17JM-16	1	1 1/16	41,9	92,9	32	280
C21JM-16	1	1 5/16	43,6	94,6	34	280
C26JM-16	1	1 5/8	46,8	97,8	42	280
C26JM-20	1 1/4	1 5/8	47,6	105,3	42	210
C30JM-20	1 1/4	1 7/8	52,8	110,5	50	185
C30JM-24	1 1/2	1 7/8	53	117,5	50	185
C40JM-32	2	2 1/2	63,4	133,4	65	175

* Attentie: let ook op de maximale werkdruk van de slang.