

Type T3A 90S-4

Cod. R090S401,1BA5A00000T

Mounting position

IM	B34
IM	2101

*Drawings available upon request*


Electrical data				General data			
Rated motor power	1.1		Kw	Frame size	90		
Rated motor speed	1440		min <sup>-1</sup> 50Hz	Mounting	B34		
	1730		min <sup>-1</sup> 60Hz	Weight	15.25	Kg	
Rated motor frequency	50		Hz	Casing material	Aluminum		
Rated motor voltage(+/-10%)	230		VΔ/50Hz	Protection	IP	55	
	400		VY/50Hz	Insulation class	H		
	280		VΔ/60Hz	Tropicalization	Yes		
	480		VY/60Hz	Vibration class	A		
Rated motor torque	7.3		Nm (Mn)	Duty	S1		
Rated motor current	4.44	VΔ/50Hz	A (In)	Direction of rotation	Bidirectional		
	2.57	VY/50Hz	A (In)	Method of cooling	IC	411	
Starting motor current	7.1		xIn	Cable entry	1-M20x1,5		
Starting motor torque	4		xMn	Standards	IEC/DIN/ISO/VDE/EN		
Breakdown motor torque	3.4		xMn	Execute at Standard	IEC 60034-1		
Starting			D.O.L.	Feet removable	Yes		
Efficiency class	IE3			Paintwork	7024	C2 standard	
Efficiency	50Hz	60Hz		Thermal protections	n/a		
	84.1	84.3	100% load	<b>Site conditions</b>			
	84.1	83.7	75% load	Ambient temperature	from -20°C to +40°C		
	81.8	83	50% load	Altitude above sea level	1000 m		
Power factor cosφ	0.74	0.74	100% load				

Mechanical data				
Noise level	LpA	70	dB(A)	
	LwA	80	dB(A)	
Moment of inertia	0.00384		Kgm <sup>2</sup>	
Bearings type			NSK	
Lubricants for bearings	See installation and maintenance manual		Bearing DE side	6205-2RS-C3
			Bearing NDE side	6205-2RS-C3
			Average bearing lifetime	40000 h
			Relubrication interval L1 DE bearing	life h
			Relubrication interval L1 NDE bearing	life h
			Compensation ring	NDE SIDE standard


There may be differences between rating plate and calculated values.



NO LOAD



LOCKED ROTOR



LOAD

