



THREADED CARTRIDGE MOUNTED SINGLE-ACTING VALVES

They allow free flow in one direction, shutting-off the return flow in the opposite direction. Release pressure 0,35 bar.
On request calibration at 2, 4, 6, 8, 10 bar.

On request

- Version in AISI 316 code FT 2267/6
- Complete with Viton seals (V)



FT 267/6

VALVE SEATING SIZE TABLE

TYPE	A	Ø B	C	D	Ø E	F	Ø G	H	Ø K	L	
	UNI 4534									MIN	MAX
1 4	M22x1,5	20,5	16,5	13,5	19	45,5	10	52	8	33,5	36
3 8	M27x2	25	18	16	24	52,5	15	59	10	36,5	40
1 2	M33x2	31	21	17	29	63,5	20	71	12	45	49
3 4	M42x2	40	25	20	38	76	26	85,5	15	52	59

TECHNICAL DATA

TYPE	MAX. WORKING PRESSURE BAR	MIN. BURSTING PRESSURE BAR	WORKING TEMPERATURE °C	FILTRATION GRADE µM ABSOLUTE
1 4	320	1300	-20°/+100°	25
3 8	320	1300	-20°/+100°	25
1 2	320	1300	-20°/+100°	25
3 4	320	1300	-20°/+100°	25
1 0 0	320	1300	-20°/+100°	25